

## Technical data sheet Version 2

## Acrylic wall paint ТУ 2316-005-49630959-04

**Purpose** For high-quality decorative finishing of brick, concrete, plastered, wooden and other surfaces (except floors) inside the premises.

**Properties** Forms a matte, uniform, smooth, vapor permeable coating. Can be tinted with water and universal tinting pastes in pastel shades. Suitable for hand and machine tinting.

**Composition** Water  
Micronized marble  
Acrylic latex  
Titanium Dioxide  
Targeted micro-additives

**Packing** Plastic containers weighing 1.4 kg, 3 kg, 6.5 kg, 13 kg, 35 kg

### Technical Specifications

Appearance	Homogeneous mass of white color
Film appearance after drying	Smooth, no visible inclusions
Bruckfield viscosity, cPs, sp. 5, V=20 rpm, 25°C	5000-6000
Grind degree, μm, not more	30
Mass fraction of non-volatile substances, %, no less	50
Frost resistance, cycles	5
pH	6,5-9,6
Temperature of application, °C, not less	+8
Drying time up to degree 3	1
at (20±2) °C, hour, not more	24
Total drying time, hour	150 г/м <sup>2</sup>

**Storage conditions** Store in a tightly closed container, away from heaters and direct sunlight, at a temperature not lower than +5°C. In case of freezing products thaw at room temperature and mix thoroughly until homogeneous mass. After thawing it completely retains its properties.

---

**Guaranteed shelf life** In unopened container manufacturer 24 months from the date of manufacture.

---

**Transportation** By all means of transport in conditions excluding the influence of atmospheric factors (covered vans, wagons, etc.). Duration of transportation at temperatures below 0°C should not exceed 1 month. Product does not belong to dangerous goods. Code of emergency measures is not required.

---

**Waste management** Containers and unused paint residue are disposed of as household waste after drying.

---

**Safety** The paint is flame retardant and non-toxic. Use personal protective equipment. When using the product do not smoke, do not drink, do not eat. In case of contact with skin and eyes wash with water. Keep out of reach of children. Avoid contact with water and soil.

---

All information is correct on the day of publication. Published technical data and instructions are subject to change without notice.